

U.S.S.N. 10/710,897

2

04966 (LC 0163 PUS)

In the claims:

1. (Currently Amended) A vehicle overhead module powerstrip assembly comprising:

at least one overhead attachment strip configured to couple to a vehicle overhead structure;

at least one electrically conductive strip coupled to said at least one attachment strip; and

~~at least one~~ a plurality of modular connector connectors each of which comprising a plurality of electrical contacts having a plurality of attachment positions along said at least one electrically conductive strip, said ~~at least one~~ plurality of modular connector connectors removable from said at least one electrically conductive strip, position interchangeable with each other, and configured to couple at least one overhead electronic module to said at least one electrically conductive strip.

2. (Original) An assembly as in claim 1 wherein said at least one attachment strip is in the form of a single extruded component.

3. (Original) An assembly as in claim 1 wherein said at least one attachment strip comprises at least one flange that covers at least a portion of said at least one electrically conductive strip.

4. (Currently Amended) An assembly as in claim 3 wherein said at least one flange is flexible and flexes outward when said plurality of modular connectors are removed to at least partially cover and prevent access to said at least one conductive strip.

5. (Canceled)

6. (Original) An assembly as in claim 3 wherein said at least one flange applies pressure on said at least one modular connector to maintain electrical contact between said at least one electrically conductive strip and said at least one modular connector.

7. (Original) An assembly as in claim 1 wherein said at least one electrically conductive strip comprise:

U.S.S.N. 10/710,897

3

04966 (LC 0163 PUS)

a positively charged electrically conductive strip; and
a negatively charged electrically conductive strip.

8. (Original) An assembly as in claim 1 wherein said at least one electrically conductive strip extend in a fore and aft direction along a longitudinal centerline of a vehicle.

9. (Currently Amended) An assembly as in claim 1 wherein said plurality of electrical contacts comprises a ~~spring-loaded~~ ground contact, having spring characteristics, such that it is in compression when ~~that is~~ in contact with a ground strip of said at least one electrically conductive strip.

10. (Original) An assembly as in claim 1 wherein said at least one overhead attachment strip comprises a plurality of channels, at least a portion of said plurality of electrical contacts extend into said plurality of channels and are in contact with said at least one electrically conductive strip therein.

11. (Original) An assembly as in claim 1 wherein said plurality of electrical contacts comprise:

a first power contact; and

a second power contact having a physical spreading resistance relative to said first power contact to maintain electrical contact with said at least one electrically conductive strip.

12. (Original) An assembly as in claim 1 wherein said plurality of electrical contacts are slidable along said at least one electrically conductive strip.

13. (Currently Amended) An assembly as in claim 1 wherein said at least one overhead attachment strip further comprises a main center member and wherein said at least one electrically conductive strip comprises a power strip and a ground strip that are, said at least one electrically conductive strip coupled to and ~~extending~~extend along said main center member.

U.S.S.N. 10/710,897

4

04966 (LC 0163 PUS)

14. (Currently Amended) An assembly as in claim 1 wherein said at least one modular connector comprises at least one insulator separating said plurality of electrical contacts, said at least one insulator comprises a plurality of module attachment holes for attaching said at least one insulator to said overhead electronic module.

15. (Canceled)

16. (Currently Amended) A vehicle overhead console comprising:

at least one track;

~~at least one~~ a plurality of overhead electronic module console modules transitional and position interchangeable along said at least one track; and

at least one vehicle overhead module powerstrip assembly comprising;

at least one overhead attachment strip configured to couple to a vehicle overhead structure;

at least one electrically conductive strip coupled to said at least one attachment strip; and

~~at least one~~ a plurality of removable and modular ~~connector~~ connectors coupled to said plurality of overhead modules and comprising a plurality of electrical contacts having a plurality of attachment positions along said at least one electrically conductive strip, ~~said at least one~~ plurality of removable and modular ~~connector~~ connectors configured to couple and allow separation of said ~~at least one~~ plurality of overhead electronic ~~module~~ modules to and from said at least one electrically conductive strip.

17. (Original) A console as in claim 16 wherein said at least one overhead attachment strip is coupled to said at least one track via at least one fastening device.

18. (Original) A console as in claim 16 wherein said at least one electronic module has an infinite number of module positions relative to

U.S.S.N. 10/710,897

5

04966 (LC 0163 PUS)

said track and receives power from said at least one electrically conductive strip in each of said module positions.

19-20. (Canceled)

21. (Previously Presented) An assembly as in claim 1 wherein said overhead electronic module is a non-illumination providing module.

22. (Previously Presented) An assembly as in claim 1 wherein said overhead electronic module is selected from at least one of a garage door opener module, an audio module, a video module, an HVAC module, and a display module.

23. (New) A console as in claim 16 wherein said plurality of overhead modules comprise a plurality of electronic modules.

24. (New) A vehicle overhead console comprising:
at least one track;
at least one vehicle overhead console module powerstrip assembly coupled to said at least one track and comprising;
at least one overhead attachment strip configured to couple to a vehicle overhead structure; and
at least one electrically conductive strip coupled to said at least one attachment strip; and
a plurality of overhead modules transitional, removable, and position interchangeable along said at least one track and comprising at least one modular connector having at least one electrical contact for coupling to said at least one electrically conductive strip.